

COMPEX™ PMV40 Vacuum Bag Connector

DESCRIPTION

The solid body design of the PMV40 combines the male quick disconnect and thru-bag connector, eliminating threaded connections and potential leak paths. Robust stainless steel construction ensures corrosion resistance and long life. High temperature O-ring and platinum cured silicone gasket give a long service. It is fully compatible with 1/4" ISO-B "Hansen" style quick disconnects. The valve mechanism and O-ring seals can easily be replaced to extend life.

- Design eliminates threaded plug connection and all risk of vacuum leakage.
- Seals and valve parts can be easily be replaced to extend life.
- Stainless steel construction means no coating breakdown at high temperature.



TECHNICAL DATA

Construction	2 pieces: Base plate, top piece
Material Type	Stainless steel
Material Type of Gasket	Silicone
Coupling Size	1/4 inch
Assembly Style	Screw down
Service Temperature	260°C

SIZE

Product	Base Plat Diameter
PMV40	60mm (2,38 inches)

INSTRUCTION TO USE

- Insert the base under the vacuum bag.
- A small cut is made in the vacuum bag in the area for the round opening in the base plate.
- The top piece of the valve is inserted through the vacuum bag and threaded into the base.
- Maintenance seals removable through base.

CONTACT US:

Stockholmer Platz 1, 70173, Stuttgart, Germany
+49 711 87089000
info@apspolymer.de
www.apspolymer.de

For UK:

www.apspolymer.co.uk
sales@apspolymer.co.uk