

Ideally suited to aerospace applications.

## FEATURES & BENEFITS

- Porous nylon peel ply.
- Heat set and scoured, for use directly against laminates or bond lines.
- Imparts a coarse weave pattern upon removal from the laminate.
- Strips cleanly and quickly from most commercial resin systems.
- Available coated or non-coated depending on user requirement.
- Recommended for composite manufacture and metal bonding applications.
- APS Polymer does not recommend the use of woven nylon fabrics with phenolic resin or prepreg systems as acid in the catalyst can break down nylon materials. Therefore, we recommend that customers conduct their own internal compatibility tests.

## PROPERTIES

Maximum use temperature	204°C / 400°F
Color	PP100: White / PP100PS: White with red tracer
Fabric type	Nylon
Fabric weight	85g/m <sup>2</sup> / 2.51oz/yd <sup>2</sup>

## AVAILABILITY

Standard width	1.52m	60in
Standard length	100m	109yd
Slit widths available to order		

## STORAGE

No special storage conditions required.

## HEALTH & SAFETY

Please refer to the product MSDS for safe handling, personal protective equipment recommendations and disposal considerations.

### CONTACT US:

Stockholmer Platz 1, 70173, Stuttgart, Germany  
+49 711 87089000  
info@apspolymer.de  
www.apspolymer.de

### For UK:

www.apspolymer.co.uk  
sales@apspolymer.co.uk