

COMPEX™ ST-A180
Sealant Tape



Ideally suited to aerospace applications.

FEATURES & BENEFITS

- Bespoke formulation mixed and extruded on state of the art equipment.
- High tack and elongation for adhesion to vacuum bag and quick efficient pleating.
- Durable tape suitable
- Optimised strip characteristics from all tooling surfaces when compared to other brands of tape currently available.
- High quality product designed specifically for composite/metal bonding applications in both oven and autoclave cures.

PROPERTIES

Maximum cure temperature	180°C bag to tool (195°C allowable peak) 190°C bag to bag (205°C allowable peak)	302°F bag to tool (383°F allowable peak) 356°F bag to bag (401°C allowable peak)
Color	Cream	

AVAILABILITY

Roll size	7.6m x 13mm x 3mm	25ft x 0.5in x 0.125in
Standard box contents	40 rolls per box	

STORAGE

Must be stored in its original containers, below 27°C (81°F).
Material has a 12 month shelf life from date of manufacture.
Must be stored flat.
Boxes should be stacked no more than 5 high.

HEALTH & SAFETY

Please refer to the product MSDS for safe handling, personal protective equipment recommendations and disposal considerations.

CONTACT US:

Stockholmer Platz 1, 70173, Stuttgart, Germany
+49 711 87089000
info@apspolymer.de
www.apspolymer.de

For UK:

www.apspolymer.co.uk
sales@apspolymer.co.uk

