

COMPEX™ ST-W180
Sealant Tape



Ideally suited to wind energy applications.

FEATURES & BENEFITS

- Specially formulated with a cost optimized design suitable for ambient, debulk and medium temperature applications.
- Widely used in the wind, marine and glass industries.
- Excellent tack.
- Also suitable for high temperature envelope bagging applications.
- Material compatible with most substrates (including composite tools) and film materials.
- For optimum results, tape must be allowed to cool to an ambient temperature before stripping from mould surfaces.

PROPERTIES

Maximum cure temperature	150°C bag to tool 180°C bag to bag	302°F bag to tool 356°F bag to bag
Color	Black Gray	

AVAILABILITY

Roll size	15m x 12mm x 3mm	49ft x 0.5in x 0.125in
	Also available as a 4mm (0.16in) diameter bead	
Standard box contents	22 rolls per box	

STORAGE

Must be stored in its original containers, under optimum conditions of between 5 and 25°C (41°F and 77°F).
Material has a 2 year shelf life from date of manufacture.
Must be stored flat.
Boxes should be stacked no more than 5 high.

HEALTH & SAFETY

Please refer to the product MSDS for safe handling, personal protective equipment recommendations and disposal considerations.

CONTACT US:

Stockholmer Platz 1, 70173, Stuttgart, Germany
+49 711 87089000
info@apspolymer.de
www.apspolymer.de

For UK:

www.apspolymer.co.uk
sales@apspolymer.co.uk

