

COMPEX™ ST-WA204 Sealant Tape

Ideally suited to wind energy and automotive applications.

FEATURES & BENEFITS

- Ideal for ambient, oven and autoclave curing temperatures of up to 204°C (400°F).
- Uses include debulking and composite curing.
- Good level of tack against all tool surfaces.
- Maintains adhesion during low temperature cycling.
- Strips very cleanly and quickly from mold surfaces, both hot and cold.
- Tenacious adhesion to all commonly used vacuum bagging films.

PROPERTIES

Maximum cure temperature	204°C	400°F
Color	Yellow	

AVAILABILITY

Roll size	9.14m x 12mm x 3mm	30ft x 0.5in x 0.125in
Standard box contents	32 rolls per box	

STORAGE

Must be stored in its original containers, below 27°C (81°F).
Material has a 12 month shelf life from date of manufacture.
Must be stored flat.
Boxes should be stacked no more than 5 high.

HEALTH & SAFETY

Please refer to the product MSDS for safe handling, personal protective equipment recommendations and disposal considerations.

CONTACT US:

Stockholmer Platz 1, 70173, Stuttgart, Germany
+49 711 87089000
info@apspolymer.de
www.apspolymer.de

For UK:

www.apspolymer.co.uk
sales@apspolymer.co.uk