



## PERFORMANCE

<b>Solids</b>	: >99%
<b>Specific Gravity (g/cm<sup>3</sup>)</b>	: 1.4±0.1g/cm <sup>3</sup>
<b>Service Temperature Range</b>	: -40°C to 180°C
<b>Application Temperature Range</b>	: 5°C to 50°C
<b>Life Expectancy</b>	: 20 Years
<b>Penetration 1/10MM, 20°C±2 ,ISO G 5S</b>	: 65±10
<b>Heat Resistance</b>	: 120°C for 12 hours, 180°C for 3 hours.
<b>Shear Strength</b>	: ≥0.06MPa

## PRODUCT DESCRIPTION

Compex™ W-700 Sealant Tape is developed for blade and aerospace industry, yacht industry, etc. Based on advanced technology, the products have high surface adhesion force on vacuum bag and a variety of tools. In the curing cycle it has excellent seal and very easy to remove from the cold or heating surface after the curing.

## USAGE/PURPOSE

Uses for sealing of the mould in blade, yacht industry.

## COLOR

Black or yellow.

## APPLICATION

All surfaces should be free from dust, grease oil, loose mortar and any other foreign material.

Apply direct onto the surface and press sufficiently along its whole length to achieve good initial adhesion;

Remove the backing paper and offer other surface to the tape and push firmly to seal across the joint.

## SIZE & PACKING

3mm x 12mm x 15m  
150m/carton

## SHELF LIFE

24 months in original packing.

## STORAGE

Stored in a dry and cool condition.

### CONTACT US:

Stockholmer Platz 1, 70173, Stuttgart, Germany  
+49 711 87089000  
info@apspolymer.de  
www.apspolymer.de

### For UK:

www.apspolymer.co.uk  
sales@apspolymer.co.uk